

# 渦輪式往復研磨機 Turbine Reciprocating Grinder

## ATU-07



轉速 Speed	往復行程 Stroke	尺寸 Dimensions	重量 Weight
30,000 rpm	0.3, 0.7, 0.9, 1.2	ø29×208 mm	204 g

- Nylon fiber case, Light weight, Acid resistance, Cold resistance
- Patent reciprocating motor, High-torque, Highly durable
- Working speed is 30,000 rpm maximum, has optional working strokes 0.3, 0.7, 0.9, 1.2 (mm)

## AIR-6570



轉速 Speed	往復行程 Stroke	尺寸 Dimensions	重量 Weight
30,000 rpm	0.3, 0.7, 0.9, 1.2	ø29×210 mm	173 g

- Nylon fiber case, Light weight, Acid resistance, Cold resistance
- Slip-proof line in the front-end
- Working speed is 30,000 rpm maximum, has optional working strokes 0.3, 0.7, 0.9, 1.2 (mm)
- High rigidity chuck, diameter 1 & 3 (mm)

## AIR-817



轉速 Speed	往復行程 Stroke	尺寸 Dimensions	重量 Weight
32,000 rpm	0.3, 0.7, 0.9, 1.2	ø30×199 mm	217 g

- Nylon fiber case, Light weight, Acid resistance, Cold resistance
- Slip-proof line in the front-end
- Working speed is 30,000 rpm maximum, has optional working strokes 0.3, 0.7, 0.9, 1.2 (mm)
- High rigidity chuck, diameter 1 & 3 (mm)

## ARA-600U



轉速 Speed	往復行程 Stroke	尺寸 Dimensions	重量 Weight
30,000 rpm	0.3, 0.7, 0.9, 1.2 mm	ø29×200 mm	230 g

- Slip-proof line in the front-end
- Working speed is 30,000 rpm maximum, has optional working strokes 0.3, 0.7, 0.9, 1.2 (mm)
- High rigidity chuck, diameter 1 & 3 (mm)