



AIR-4G



- Hyper operation speed that up to 80,000 rpm maximum
- Motor is assembled by 4-piece bearings
- Highly stable and good for handling

轉速 Speed	夾頭 Chuck	尺寸 Dimensions	重量 Weight
80,000 rpm	ø 3 mm	ø17×159 mm	169 g

AIR-8G



- Hyper operation speed that up to 80,000 rpm maximum
- Motor is assembled by 4-piece bearings
- Chuck is changeable, chuck diameter 3, 1/8, 2.4 (mm)

轉速 Speed	夾頭 Chuck	尺寸 Dimensions	重量 Weight
80,000 rpm	ø 3, 1/8, 2.4 mm	ø18×154 mm	168 g

GT-A260



- One of best-seller products in “Lih” brand
- No-load operation speed can be 60,000 rpm maximum.
- Chuck is changeable, chuck diameter 3, 1/8, 2.4 (mm)
- Highly stable and good for handling

轉速 Speed	夾頭 Chuck	尺寸 Dimensions	重量 Weight
60,000 rpm	ø 3 mm	ø17×155 mm	169 g

AIR-3M



- One of best-seller products in “Lih” brand
- No-load operation speed can be 65,000 rpm maximum.
- Light weight, High torque, Also has a long product life
- Highly stable and good for handling

轉速 Speed	夾頭 Chuck	尺寸 Dimensions	重量 Weight
65,000 rpm	ø 3 mm	ø17×145 mm	132 g